

45x90 Rett. 18"x36" Rect. / 22,5x90 Rett. 9"x36" Rect. 60x60 Rett. 24"x24" Rect. / 40x60 Rett. 16"x24" Rect. 20x60 Rett. 8"x24" Rect. / 30x60 Rett. 12"x24" Rect. 60x60 Spz. Rett. 24"x24" Brs. Rect. 30x60 Spz. Rett. 12"x24" Brs. Rect. 30x60 Grip 12"x24" Grip / 30x30 Grip 12"x12" Grip 15x15 Grip 6"x6" Grip 60x60 Rett. Grip / 24"x24" Rect. Grip		± 10 mm ± 9,5 mm ± 20 mm	Norma. Norms. Norme. Norm. Norma. Norma.	Requisiti per misura nominale N Requirement for nominal size N. Conditions requises pour obtenir mesure nominale N. Voraussetzungen für das Nominalmaß N. Requisitos para el tamaño nominal N. Требования к номинальному размеру N.		Valore medio. Average value. Valeur Moyenne. Durchschnittswert. Valor Mediano. Среднее значение.				
				7 cm ≤ N < 15 cm	N ≥ 15 cm	Naturale	Spazzolata	Grip	Grip SP 20mm	
Lunghezza e Larghezza. Length and width. Longueur et largeur. Länge und Breite. Longitud y anchura. Длина и ширина. Spessore. Thickness. Epaisseur. Staerke. Espesor. Толщина. Rettilinearità spigoli. Straightness. Equerrage des angles. Geradlinigkeit der Kanten. Rectilineidad de los cantos. Прямолинейность ребер. Ortogonalità. Squareness. Orthogonalité. Rechtwinkligkeit. Ortogonalidad. Ортогональность.	ISO 10545-2	± 0,9 mm ± 0,5 mm ± 0,75 mm ± 0,75 mm ± 0,75 mm	± 0,6% ± 2,0 mm ± 5,0% ± 0,5 mm ± 0,5% ± 1,5 mm ± 0,5% ± 2,0 mm	Conforme. Suitable for. Conforme. Konform. Conforme. Соответствующий.						
				Assorbimento % d'acqua. Water Absorption. Absorption d'eau. Wasseraufnahme. Absorción % de agua. Водопоглощение, %.	ISO 10545-3	≤ 0,5%	≤ 0,1%	≤ 0,1%	≤ 0,1%	≤ 0,1%
					ISO 10545-4	(Spessore. Thickness. ≥ 7,5 mm) S ≥ 1300 N	S ≥ 1800 N	S ≥ 1800 N	S ≥ 1800 N	S ≥ 10.000 N
				Sforzo di rottura. Breaking strength. Force de rupture. Bruchlast. Esfuerzo de ruptura. Усилие на излом.	ISO 10545-4	R ≥ 35 N/mm ²	R ≥ 45 N/mm ²	R ≥ 45 N/mm ²	R ≥ 45 N/mm ²	R ≥ 50 N/mm ²
EN 1339	-	-	-		-	T11				
Resistenza all'abrasione profonda. Deep scratch resistance. Résistance à l'abrasion. Tiefenabriebharte. Resistencia a la abrasión profunda. Устойчивость к глубокому истиранию.	ISO 10545-6	≤ 175 mm ³	≤ 150 mm ³	≤ 150 mm ³	≤ 150 mm ³	≤ 140 mm ³				
	ISO 10545-8	Valore dichiarato (ISO 13006: metodo di prova disponibile). Declared value (ISO 13006: Test method available).	≤ 7 (MK) ⁻¹	≤ 7 (MK) ⁻¹	≤ 7 (MK) ⁻¹	≤ 6,5 (MK) ⁻¹				
Resistenza agli sbalzi termici. Thermal shock resistance. Résistance aux écarts de température. Temperaturwechselbeständigkeit. Resistencia a los choques térmicos. Стойкость к перепаду температур.	ISO 10545-9	In accordo con la EN ISO 10545-1 (ISO 13006: metodo di prova disponibile). In accordance with EN ISO 10545-1 (ISO 13006: Test method available).	Resiste. Resistant. Résistant. Beständig. Resiste. Выдерживает.							
	ISO 10545-12	In accordo con la EN ISO 10545-1 (ISO 13006: Richiesta). In accordance with EN ISO 10545-1 (ISO 13006: Required).	Resiste. Resistant. Résistant. Beständig. Resiste. Выдерживает.							
Coefficiente di attrito dinamico. Dynamic friction coefficient. Coefficient de frottement dynamique. Dynamischer Reibungskoeffizient. Coeficiente de rozamiento dinámico. Устойчивость к скольжению при движении.	B.C.R.A. μ > 0,40	D.M.I. Giugno 1989 n. 236 (μ > 0,40)	> 0,40	-	> 0,40	> 0,40				
	Coefficiente di attrito statico. Coefficient of static friction. Coefficient de frottement statique. Statischer Reibungskoeffizient. Coeficiente de rozamiento estático. Устойчивость к скольжению при статической нагрузке.	ASTM C 1028 (S.C.O.F.)	≥ 0,60 ASCIUTTO ≥ 0,60 BAGNATO ≥ 0,60 DRY ≥ 0,60 WET	≥ 0,60 DRY ≥ 0,60 WET	-	≥ 0,60 DRY ≥ 0,60 WET	≥ 0,60 DRY ≥ 0,60 WET			
		ANSI A137.1:2012 (D.C.O.F.)	≥ 0,42 BAGNATO ≥ 0,42 WET	≥ 0,42 WET	-	≥ 0,42 WET	≥ 0,42 WET			
	Resistenza allo scivolamento. Slip resistance. Résistance au glissement. Rutschfestigkeit. Resistencia al deslizamiento. Сопротивление скольжению.	BS7976-2:2002 Pendulum Testers	Bassa potenzialità di scivolamento. Low slip risk. ≥ 36 ASCIUTTO ≥ 36 BAGNATO ≥ 36 DRY ≥ 36 WET	≥ 36 DRY ≥ 36 WET	-	≥ 36 DRY ≥ 36 WET	≥ 36 DRY ≥ 36 WET			
		DIN 51130	In funzione dell'ambiente o della zona di lavoro. Based on the environment or on the working area.	R10	R9	R11	R11			
Classificazione antiscivolo (Piedi nudi). Non-slip classification (Barefoot). Classification antidérapement (Pieds nus). Trittsicherheitsklassen (Barfuß). Classificación antideslizamiento (Pies descalzos). Классификация противоскользящей плитки (Босые ноги).	DIN 51097	Secondo la classificazione indicata dal fabbricante. Manufactured to state classification.	-	-	A+B+C	A+B+C				
	ISO 10545-13	Valore dichiarato (ISO 13006: secondo la classificazione indicata dal fabbricante). Declared value (ISO 13006: Manufacturer to state classification).	ULA	ULA	ULA	ULA				
Resistenza ai prodotti chimici di uso domestico ed agli additivi per piscina. Resistance to household chemicals and swimming pool salts. Résistance aux produits chimiques à usage domestique et aux adjuvants pour piscines. Beständigkeit gegen Haushaltschemikalien und Badewassersätze. Resistencia a los productos químicos de uso doméstico y a los aditivos para piscinas. Устойчивость к воздействию химических средств домашнего использования и химических добавок для бассейна.	ISO 10545-13	Classe UB min.	UA	UA	UA	UA				
		Valore dichiarato (ISO 13006: metodo di prova disponibile). Declared value (ISO 13006: Test method available).	UHA	UHA	UHA	UHA				
Resistenza alle macchie. Resistance to stains. Résistance aux taches. Fleckenbeständigkeit. Resistencia a las manchas. Тойкость к образованию пятен.	ISO 10545-14	Valore dichiarato (ISO 13006: metodo di prova disponibile). Declared value (ISO 13006: Test method available).	Pulibile. Cleanable. Nettoyable. Kann gereinigt werden. Limpiable. Моющийся.							